


## **REAR OF VEHICLE**

WIRING KEY								
PIN	COLOR	COMPONENT	TYP. MAX CURRENT(A)	COMMENT				
N/A	RED	ROTATORS - OUTER	10.2					
N/A	BLK	GROUND	40A Limit	RING TERMINAL				

## **SPECIFICATIONS**

- 1. FLASH MODE: MAXIMUM: 640 FPM
- 2. VOLTAGE (NOMINAL): 12 VDC
- 3. CURRENT (NOMINAL): 10.2 A 4. CONNECTION: 14 OR 16 AWG WIRES IN CABLE
- 5. MOUNTING: 4-BOLT THROUGH MOUNTING KIT
- 6. BASE MATERIAL: ALUMINUM
- 7. LENS MATERIAL: POLYCARBONATE



## NOTES:

- 1. CABLES AND WIRING NOT SHOWN
- 2. TOP VIEW: TOP LENSES NOT SHOWN FOR CLARITY
- 3. MOUNTING FEET: ADD 30mm TO OVERALL HEIGHT
- 4. THE LENGTH BETWEEN MOUNTING FEET IS ADJUSTABLE
- 5. CABLE LENGTH 0.94m[3.0'] FROM INTERNAL CONNECTOR 6. CABLE EXIT DRIVER'S SIDE
- 7. DIMENSIONS IN MILLIMETERS [INCHES (FOR REFERENCE)]

THE DRAWING AND THE DESIGN IT DISCLOSES ARE THE PRIVATE PROPERTY OF ECCO AND IS ISSUED IN CONFIDENCE FOR ENGINEERINGINFORMATION )
MIN, THE DRAWING AND / OR BESIGN MAN YOLD BE USED, COPIED, BEPRODUCED, OR OTHERWISE DISCLOSED IN PROCESSED AS A WHOLE TO DUISTIDERS OF USED FOR ANY OTHER PURPOSE WITHOUT THE PRIOR WRITTEN CONSENT OF ECCO. THE DRAWING IS SUBJECT TO RECALL AT ANY TIME, YOUR POSSESSION OF THIS DOCUMENT CONSTITUTES ACCEPTANCE OF THESE TERMS, © 2002 ECCO.

		APPROVALS DRAWN BY RDE	DATE			Electronic Controls Co 833 West Diamond Street, Boise,ID 83705		•
	SCALE 1:8.5 CAD GENERATED DRAWING	CHECKED		LU		800-635-5900 www.eccolink.com		
	DO NOT MANUALLY UPDATE. MODEL REFERENCED:A			LBR,60,12V,22"/0.57M,143-00220-60				
	TOLERANCES ARE IN MILLIMETERS, AND INCHES TOLERANCES ARE:  MILLIMETERS DECIMALS XX.X ± 5mm XX.X ± 0.2 ± 0.5			CUSTOMER PART NO. 6221003			PRODUCT SERIES: 60 Series Lightk	
THIRD ANGLE PROJECTION				SIZE: . D	WG. NO.	622100	3	Γ

es Lightbar 6221003 В SHEET 1 OF 1 Project: 00012 Date Created: 2002-01-09